



SECTION B-B

P. C. B LAYOUT

SECTION C-C

SPECIFICATION:  
1.MATERIAL:  
HOUSING: LCP 30% G/F UL 94V-0  
COLOR:BLACK  
CONTACT:BRASS C2680R EH,T=0.25mm  
PEG: BRASS C2680R H,T=0.30mm  
2.FINISH:  
CONTACT: (3u"/15u") GOLD/TIN PLATING ON CONTACT AREA  
100u" MIN. TIN-LEAD PLATING ON SOLDER TAILS  
50u" MIN.NICKEL UNDERPLATING OVER ALL  
PEG: 100u" MIN. TIN-LEAD PLATING ON SOLDER TAILS  
50u" MIN.NICKEL UNDERPLATING OVER ALL

鉅創科技有限公司  
TRONTEK TECHNOLOGY CO.,LTD.

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.X' ±2" X.X' ±0.5"	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: SATA 7PIN 半包正向SMT
UNIT: mm [inch]	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. MOLD NO.
SCALE:1:1 SIZE: A4	APPROVED BY: 邱国夷	DATE : 2014-02-23	DRAW NO: SHEET NO.
			1 OF 1