



RECOMMEND PCB LAYOUT
PCB TOLERANCE:±0.05

NOTES:
1. MATERIAL:
HOUSING: LCP 30% G/F UL94 V-0
COLOR: BLACK

CONTACT: BRASS C2680H T=0.25mm
BOARD LOCK: BRASS C2680H T=0.30mm
2. FINISH:

CONTACT: GOLD FLASH/MATTE TIN PLATING ON CONTACT AREA
100u" MIN. MATTE TIN PLATING ON SOLDER TAILS
50u" MIN. NICKEL UNDERPLATING OVER ALL
BOARD LOCK: 100u" MIN. MATTE TIN PLATING ON SOLDER TAILS
50u" MIN. NICKEL UNDERPLATING OVER ALL

鉞創科技有限公司

TRONTEK TECHNOLOGY CO., LTD.

TOLERANCE:		DRAWN BY :		DATE :		PART NAME:	
XX ±0.30		SANDY		2017.5.18		SATA 7P 180度DIP 開窗A型	
XXX ±0.25		CHECKED BY :		DATE :		PART NO.	
XXXX ±0.15		DAVID		2017.5.18		TS-A30-SATA-110	
X' ±2°		APPROVED BY :		DATE :		MOLD NO.	
UNIT: mm [Inch]		JACK		2017.5.18		DRAW NO.:	
SCALE: 1:1		SIZE: A4				SHEET NO.	
						10F1	