



规格说明: Specifications:

电气特性: Electrical:

- 额定电流: Current Rating
1.0A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触阻抗: Contact Resistance
50 milliohms MAX
- 耐电压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level
- 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force: 3.0kgf (MAX)
Unmate force: 0.7kgf (MIN)
- 端子保持力: Terminal Retention
0.5kgf (MIN)

原材料: Material:

- 塑胶: Housing:
High Temperature Thermoplastics,
UL 94V-0 LCP Black
- 端子: Contact: Copper Alloy C5191
- 外壳: Shell: Copper Alloy C2680

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
- 外壳: Shell:
Nickel Plating

鉍創科技有限公司

TRONTEK TECHNOLOGY CO., LTD.

TOLERANCE: XX ± 0.30 XXX ± 0.25 XXXX ± 0.15	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: MICRO USB SP B/D 端子加长0.56 四脚DIP	
X' $\pm 2'$ X.X' $\pm 0.5'$	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. TMC64-USBD05-180	
UNIT: mm [Inch]	APPROVED BY: 邱国夷	DATE : 2014-02-23	MOLD NO.	DRAW NO.
SCALE: 1:1	SIZE: A4		SHEET NO.	1 OF 1