



RECOMMENDED PCB LAYOUT (TOP VIEW)
GENERAL TOLERANCES: ±0.05

NOTES:

1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC FLAMMABILITY RATING UL94V-0
 - 1.2 CONTACT: COPPERY ALLOY T=0.15mm
 - 1.3 SHELL: STAINLESS STEEL T=0.25mm
2. FINISH:
 - 2.1 CONTACT: 30' Min. PLATED ON CONTACT AREA
 - 2.2 SHELL: G/F PLATING ON SOLDER TAIL AREA
3. SPECIFICATION:
 - 3.1 CURRENT RATING: 1.0A MAX
 - 3.2 VOLTAGE: 100 VAC
 - 3.3 TEMPERATURE RANGE: -30 °C ~ 85 °C
 - 3.4 CONTACT RESISTANCE: 30 MILLIONHM MAX
 - 3.5 DIELECTRIC WITHSTANDING VOLTAGE: 200 VAC r.m.s
 - 3.6 INSULATION RESISTANCE: 100 MEGOHMS MIN.

<p>鉅創科技有限公司 TYRONTEK TECHNOLOGY CO., LTD.</p>		<p>DRAWN BY : SANDY DATE : 2016-08-16</p>		<p>CHECKED BY : TONY DATE : 2016-08-16</p>		<p>APPROVED BY : DAVTD DATE : 2016-08-16</p>	
<p>TOLERANCE: XX ±0.30 XXX ±0.25 XXXX ±0.15 X' ±2' X' ±0.5'</p>		<p>PART NAME: Micro usb 5P/F B Type SM+HP 5.65(有粘)</p>		<p>PART NO. TMCO1-USB005-565</p>		<p>MOLD NO. TMCO1-USB005-565</p>	
<p>UNIT: mm [inch] SCALE:1:1 SIZE: A4</p>		<p>DRAW NO.: TMCO1-USB005-565</p>		<p>SHEET NO.</p>			