



- NOTES:
- MATERIAL:
    - HOUSING: THERMOPLASTIC FLAMMABILITY RATING UL94V-0
    - CONTACT: COPPERY ALLOY T=0.15mm
    - SHELL: STAINLESS STEEL T=0.25mm
  - FINISH:
    - CONTACT:
      - 3u"Min. PLATED ON CONTACT AREA
      - G/F PLATING ON SOLDER TAIL AREA
      - 50~80u" NICKEL UNDERPLATING OVERALL
    - SHELL:
      - 80~120u" MATTER TIN PLATING ALL
      - 50~80u" NICKEL UNDERPLATING OVERALL
  - SPECIFICATION:
    - CURRENT RATING: 1.0A MAX
    - VOLTAGE: 100 VAC
    - TEMPERATURE RANGE: -30 °C ~ 85 °C
    - CONTACT RESISTANCE: 30 MILLIONHM MAX
    - DIELECTRIC WITHSTANDING VOLTAGE: 200 VAC r.m.s
    - INSULATION RESISTNACE: 100 MEGOHMS MIN.

鉍創科技有限公司  
TRONTEK TECHNOLOGY CO.,LTD.

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: MICRO USB 5.65 TYPE加固无卷边	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. TMC04-USB05-565	MOLD NO.
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY: 邱国夷	DATE : 2014-02-23	DRAW NO:	SHEET NO. 1 OF 2