



-NOTES-

1. Electrical:
 Contact resistance: 50m ohms max.
 Dielectric withstanding voltage:
 250V RMS.
 Insulation resistance:
 50M ohms min.
2. Mechanical:
 MATE AND UNMATE FORCE:
 MATE FORCE: 3.0kg MAX
 UNMATE FORCE: 1.02kg MIN
 Durability: 3000cycles MIN.
3. Environment:
 Operating
 Temperature: -20° to +85° .
4. FINISH:
 TERMINAL: GOLD Plated Over NICKEL
 Contact area, TIN ON
 SOLDER TAIL AREA.
 SHELL: BRASS WITH TIN Plated.
5. COLOR:
 HOUSING: BLACK.

鉅創科技有限公司 TRONTEK TECHNOLOGY CO., LTD.			
TOLERANCE: XX ±0.30 XXX ±0.25 XXXX ±0.15	DRAWN BY : ANDY	DATE : 2015-7-13	PART NAME: MICO_USB_AB_TYPE_180D
UNIT: mm [Inch]	CHECKED BY: TONY	DATE : 2015-7-23	PART NO.: TMC18-(USB)05-710
SCALE: 1:1	APPROVED BY: KIN	DATE : 2015-7-23	MOLD NO.:
SIZE: A4			DRAW NO.: 3
			SHEET NO.: 4