



- 备注:
- 产品规格:
 - 1-1. 插入力: 35N MAX.
 - 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER 3000 CYCLES
 - 1-3. 额定电流: 1.0A
 - 1-4. 额定电压: 30V
 - 1-5. 耐久性: 3000 CYCLES MIN.
 - 1-6. 耐电压: 100V AC MIN.
 - 1-7. 接触阻抗: 30mΩ MAX. INITIAL: 40mΩ MAX AFTER 3000 CYCLES
 - 1-8. 绝缘电阻: 100MΩ MIN
 - 1-9. 工作温度: -30° TO +80°
 - 材质:
 - 2.1 胶芯: LCP UL94V-0
 - 2.2 端子: C2680R-H, 镍底, 镀金1μ"
 - 2.3 外壳: C2680R-H, 表面镀镍100μ
 - 所用材质须符合RoHS要求

P. C. B LAYOUT

鉅創科技有限公司
TRONTEK TECHNOLOGY CO., LTD.

TOLERANCE: XX ±0.30 XXX ±0.25 XXXX ±0.15		DRAWN BY: ANDY		DATE: 2015-6-23		PART NAME: MICRO_USB_B_TYPE_1800	
X: ±2° X' ±0.5°		CHECKED BY: TONY		DATE: 2015-6-23		PART NO. TWC12-USBD05-715	
UNIT: mm [inch]		APPROVED BY: KIM		DATE: 2015-6-23		DRAW NO: 3	
SCALE: 1:1		SIZE: A4				SHEET NO. 4	