



- Note:
 1. Specification:
 1.1 Current rating: 1 A Max.
 1.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
 1.3 Contact resistance: 50 mW Max.
 1.4 Insulation resistance: 100 MW Min.
 1.5 Total mating force: 3.57 Kgf Max.
 1.6 Total unmating force: 1.0 Kgf Min. 0.81~2.05 Kgf Min.
 1.7 Temperature range: -30°C~80°C

鉍創科技有限公司
 TRONTEK TECHNOLOGY CO., LTD.

| 3 | SHELL | SUS 201 | T=0.25 | NICKEL PLATED OVERALL | 1 |
|-----|-----------|----------|--------|------------------------------|------|
| 2 | TERMINAL | C2680 | T=0.15 | Sn 80U ⁺ + Au G/F | 5 |
| 1 | HOUSING | LCP | — | BLACK UL94-V0 | 2 |
| NO. | PART NAME | MATERIAL | THICK | FINISH | Q'TY |

| | | | |
|---|---------------------|----------------------|-----------------------------------|
| TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X'X' ±0.5' UNIT: mm [inch] SCALE: 1:1 SIZE: A4 | DRAWN BY : 陈一鸣 | DATE : 2014-02-23 | PART NAME: MICRO USB 5PIN 立式贴片 |
| | CHECKED BY: 马跃 | DATE : 2014-02-23 | PART NO. TMC63-USBD05-575 |
| | APPROVED BY: 邱国爽 | DATE : 2014-02-23 | MOLD NO. |
| | | | DRAW NO. |
| | | | SHEET NO. 1 OF 1 |