

**SPECIFICATIONS:**


- VOLTAGE/CURRENT RATING: 30V/0.3A AC;
- WITHSTANDING VOLTAGE: 100V AC ONE MINUTE;
- INSULATION RESISTANCE: 50M $\Omega$  MIN;
- CONTACT RESISTANCE: 100m $\Omega$  MAX;
- OPERATING TEMPERATURE RANGE: -35° C TO 85° C.

**MATERIAL:**

- INSULATOR: LCP UL 94V-0 BLACK;
- TERMINAL: COPPER ALLOY;
- METAL FITTINGS: COPPER ALLOY.

**PLATING:**

- TERMINAL: GOLD PLATING, NICKEL 50u" MIN. OVER ALL;
- METAL FITTINGS: TIN 100u" MIN. OVER NICKEL 50u"MIN.



PIN NO.	A	B	C
10	4.50	3.40	1.60
12	4.90	3.80	2.00
16	5.70	4.60	2.80
20	6.50	5.40	3.60
24	7.30	6.20	4.40
30	8.50	7.40	5.60
34	9.30	8.20	6.40
40	10.50	9.40	7.60
50	12.50	11.40	9.60
60	14.50	13.40	11.60
70	16.50	15.40	13.60

△	DATE	ECR	<b>鉅創科技有限公司</b> TRONTEK TECHNOLOGY CO.,LTD.				PART NAME: BTB P0.40 SOCKET	S/C NO	TOLERANCE:			
							PART NO.: BTB04F-XXP08HB		X. $\pm 0.5$	.X $\pm 2^\circ$		
			APPROVED	CHECKED	DRAWING	DWG NO.	DATE	REV	SCALE	UNIT	SHEET	.XX
								A	FIT	mm	10F1	.XXX $\pm 0.10$

