



- Note:
1. Material:
 - 1.1 Housing: High temperature thermoplastic with g.f.Ul94v-0
 - 1.2 Contact: copper alloy, t=0.20mm
 - 1.3 Shell: copper alloy, t=0.25mm
 2. Specification:
 - 2.1 Current rating: 1 A Max. voltage: 100 V(ac) for 1 min.
 - 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - 2.3 Contact resistance: 50 mW Max.
 - 2.4 Insulation resistance: 100 MW Min.
 - 2.5 Total mating force: 3.57 Kgf Max.
 - 2.6 Total unmating force: 1.0 Kgf Min. 0.81~2.05 Kgf Min.
 - 2.7 Temperature range: -30°C~80°C

鉸創科技有限公司

TRONTEK TECHNOLOGY CO., LTD.

TOLERANCE:		DRAWN BY :		DATE :		PART NAME:	
X.X	±0.30	DAVID		2014-8-22		MICRO USB 6.4 TYPE 加固無搖擺 無柱	
X.XX	±0.25	CHECKED BY :		DATE :		PART NO.:	
X.XXX	±0.15	FRANK		2014-8-22		TMC136-USBD05-640	
X: #Z	X:X #0.5	APPROVED BY :		DATE :		MOLD NO.:	
UNIT: mm [Inch]		TONY		2014-8-22		DRAW NO.:	
SCALE:1:1	SIZE: A4					SHEET NO.:	
						10F1	