



NOTE:
 1. MATERIAL:
 1.1 HOUSING: PBT, COLOR: BLUE.
 1.2 TERMINAL: COPPER ALLOY.
 1.3 SHELL: SPCC
 1.4 SCREW: SPCC
 1.5 GROUNDING: SPCC

2. PLATING:
 2.1 CONTACT: CONTACT: 80u" Min, TIN PLATED OVERALL
 50u" Min, NICKEL UNDER-PLATED

2.2 SHELL: 50u" Min, NICKEL PLATED OVERALL
 2.3 GROUNDING: 50u" Min, TIN PLATED OVERALL.
 2.4 SCREW: 50u" Min, NICKEL PLATED OVERALL.

3. SPECIFICATIONS:
 VOLTAGE: 500 VAC(RMS) MAX.
 CURRENT RATING: 3 AMPERE PER CONTACT
 CONTACT RESISTANCE: 25 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(RMS)
 VGA TOTAL MATING FORCE: 6.0 KGF MAX.
 VGA TOTAL UNMATING FORCE: 1.0 KGF MIN.
 MATING FORCE: 5.1Kg.Max.
 UNMATING FORCE: 1.0Kg MIN.
 OPERATING TEMPERATURE: -25°C ~ +85°C

銳創科技有限公司
 TRONTEK TECHNOLOGY CO., LTD.

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15		DRAWN BY : TONY		DATE : 2014-2-23		PART NAME: HDR 3.08 母座直鎖式	
X: ±2 X.X ±0.5		CHECKED BY : DAVID		DATE : 2014-2-23		PART NO. : TDS06-HDR15B-060	
UNIT: mm [inch]		APPROVED BY : FRANK		DATE : 2014-2-23		MOLD NO. : /	
SCALE: 1:1		SIZE: A4		DRAW NO. : /		SHEET NO. : 10/11	

