



NOTE:

- 1. MATERIAL:**
 1.1 INSULATOR: PBT+30%GF, UL94V-0, COLOR: BLUE
 1.2 COVER: PBT+30%GF, UL94V-0, COLOR: BLUE
 1.3 CONTACT: COPPER ALLOY,
 1.4 SHELL: SPCC
 1.5 SQUARE RIVET: BRASS
 1.6 GROUND HARPOON: SPCC
- 2. PLATING:**
 2.1 CONTACT: TIN PLATED OVERALL
 2.2 SHELL: NICKEL PLATED OVERALL
 2.3 SQUARE RIVET: TIN PLATED OVERALL
 2.4 GROUND HARPOON: TIN PLATED OVERALL

- 3. SPECIFICATIONS:**
 VOLTAGE: 250 VAC(RMS) MAX.
 CURRENT RATING: 3 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 5000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(RMS)
 VGA TOTAL MATING FORCE: 6.0 KGF MAX.
 VGA TOTAL UNMATING FORCE: 1.0 KGF MIN.
 MATING FORCE: 5.1Kg.Max.
 UNMATING FORCE: 1.0-4.0Kg.Min.
 OPERATING TEMPERATURE: -25°C ~ +85°C

4. DESIGN STANDARD ACCORDING TO D-SUB SPECIFICATION.

鉸創科技有限公司
 TRONTEK TECHNOLOGY CO., LTD.

TOLERANCE:		DRAWN BY :		PART NAME:	
X.X	±0.30	TONY	2014-2-23	HDR3.08母座銅鎖式	
X.XX	±0.25				
X.XXX	±0.15				
X. ±Z	X.X ±0.5	CHECKED BY :	DATE :	PART NO.:	TDS25-HDR15B-048
UNIT: mm [inch]		FRANK	2014-2-23	MOLD NO.:	
SCALE: 1:1	SIZE: A4	APPROVED BY :	DATE :	DRAW NO.:	
		DAVID	2014-2-23	SHEET NO.:	10F1